



clamp[®]

▶ A TRIDON COMPANY

Product Overview





CN

↔ 9mm
ø 12-200mm
DIN3017-1
W1, W2, W4, W5



CNS

↔ 12mm
ø 12-200mm
DIN3017-1
W1, W2, W4, W5




NP

↔ 9mm
ø 12-200mm
DIN3017-1
W2, W3, W4, W5



NP

↔ 12mm
ø 12-200mm
DIN3017-1
W2, W3, W4, W5



NP with Bridge

Left or Right Hand
Multiple Bridges Available
on Request.



Micro Gear

↔ 8mm
ø 16-89mm
SAE (Perforated Band)
300SS

Other Materials Available.



Hy-Gear

↔ 12mm - 1/2"
ø 12-178mm
SAE (Perforated Band)
300SS

Other Materials Available.



Hy-Gear

↔ 14mm - 9/16"
ø 20-222mm
SAE (Perforated Band)
300SS

Lined Versions Available.



Power Gear

↔ 16mm - 5/8"
ø 25-232mm
SAE (Perforated Band)
300SS



Power Gear - Lined

↔ 16mm - 5/8"
ø 25-232mm
SAE (Perforated Band)
300SS



T-Bolt

↔ 19mm - 3/4"
ø 41-211mm
with Bridge
300SS



T-Bolt - Spring Loaded

↔ 19mm - 3/4"
ø 57-141mm
with Bridge
300SS
Carbon steel bolt



TPC

↔ 16, 20, 25, 30mm
ø 23-252mm
DIN3017-3
W2, W4, W5



TPC-S

↔ 24mm
ø 122-252mm
M8/M10 Bolt & Barrel
W4, W5



TPCN

↔ 22-24mm
ø 36-252mm
M8/M10 Bolt & Barrel
W2



Bi-Blok

↔ 30mm
ø 74-500mm
2x M10 Bolt & Barrel
W1



V Clamp

Made to Order




Quick Connect V Clamp

Made to Order



Univee Clamps

Made to Order



Pressed V Clamp

Made to Order



VN

↔ 9mm
ø 27-750mm
DIN3017-1
W2, W4



VNS

↔ 12mm
ø 44-750mm
DIN3017-1
W1, W2



Surelock

↔ 14mm
ø 13-565mm
SAE (Perforated Band)
304SS, 316SS



Snap Lock

↔ 14mm
ø 13-540mm
SAE (Perforated Band)
201SS, 410SS



MAR Exhaust Clamp

M8, M10
ø 35-125mm
U-Bolt type
Steel, Zinc Plated

**Smart Seal**

↔ 12mm - 1/2"
 ø 28-125mm
 with liner
 300SS 410SS screw

**Wave Seal**

↔ 14mm - 9/16"
 ø 26-173mm
 with liner
 300SS 410SS screw

**NP - SA**

↔ 9mm
 ø 16-140mm
 Spring assist
 W3, W4

**NP - SA**

↔ 12mm
 ø 16-140mm
 Spring assist
 W3, W4

**Flex Gear LD**

↔ 14mm - 9/16"
 ø 13-89mm
 Perforated band
 300SS, 410SS
 or carbon screw

**Flex Gear HD**

↔ 16mm - 5/8"
 ø 25-232mm
 Perforated Band
 300SS, 410SS
 or Carbon Screw

**Ear Clip - Single**

↔ 6-7.5mm Band
 ø 7-18mm
 W1, W4

**Ear Clip - Double**

↔ 6-10mm Band
 ø 5-40mm
 W1, W4

**Ear Clip - Lined**

↔ 6-7.5mm Band
 ø 7.5-19.3mm
 W1, W4

**CAW - Ear Clip**

↔ 5-7mm Band
 ø 7-18, 5mm
 W4

Other Sizes on Request.

**DCL**

↔ 8mm
 ø 8-25.5mm
 Colour Coded
 W4

Other Sizes on Request.

**Ear Clamp Tool****Pneumatic Tool**

for Ear Clamps

**BIFM**

0.8-3.5mm wire
 ø 5-61mm
 Spring Wire
 W1

**CTS**

↔ 7,8mm
 ø 5.9-21.3mm
 Spring Steel
 W1

**BIFV**

↔ 1.5-3mm Wire
 ø 9-175mm
 W1

**BEN**

↔ 9mm
 ø 7-25mm
 W1

**Heavy Bolt Clamp**

↔ 25-30mm
 ø 37-120mm
 W1

**Ezyclick**

ø 9-46mm
 Colour: Black
 PA6.6

**Herbie**

ø 5.6-169mm
 Colour: Black
 PA6.6

**Fast Clamp Kit**

↔ 9mm
 3m Band & 8 Housings
 W2-W4

**Fast Clamp Kit**

↔ 14 mm
 3m band & 8 Housings
 Blister or Casette
 W2-W4

**Fast Clamp Band**

↔ 9mm
 W2-W4

**Fast Clamp Housing**

↔ 9mm
 W2-W4

**Fast Clamp Band/Housing**

↔ 14mm
 W2-W4



Banding

↔ 6, 10, 12, 16, 19mm
L= 30m
W4*, W4, W5
201SS, 304SS, 316SS



Banding - Giant

↔ 19, 25, 32mm
L=30m
W4*, W4, W5
201SS, 304SS, 316SS



Buckle

↔ 6, 10, 12, 16, 19mm
W4*, W4, W5
201SS, 304SS, 316SS



Buckle Giant

↔ 19, 25, 32mm
W4*
201SS



SCRU LOK

↔ 12, 16, 19mm
W4*
301SS, 201SS



Valuclip

Use with Valustrap



Standard Banding Tool

↔ 6-19MM



Compact Banding Tool

↔ 6-10MM



Giant Banding Tool

↔ 10-32mm




Junior Clamp

↔ 6, 10, 12, 19mm
ø 20-114mm
W4*
201SS



Ultra Lok Clamp

↔ 19mm
ø 69-228mm
W4*
201SS



Junior Clamp Tool

Complete



Adapter for Junior Clamp

Use With and Without Vice



Ball Lok

↔ 4.6-7.9mm
L=201-1067mm
Plain 304SS
Black Epoxy Coated



Tie Lok

↔ 4.5-6.3mm
L+ 25-254mm
304SS



Tool for Ball Lok

With Cut Off Lever



Tie Lok Tool

Hand Tool



Multi Lok

↔ 7, 12mm
L= 150-600mm
Plain, 316SS
Nylon 11 Coated, Black



Cable Tie

↔ 6.3-9.5mm
L=152-610mm
Plain, 316SS
PPA Coated, Black



Manual Tensioner

For Cable Ties



Tensioning Hook

on Request.



Easy Read System

on Request.



Easy Read Carriers

on Request.



Easy Read Kit

on Request.



Embossing Tool

on Request.

**TPK DIN3016**

↔ 12, 15, 20, 25mm
 ø 5-200mm
 EPDM Liner
 W1, W3, W4, W5

**Nylon Tie**

↔ 2.2-12.5mm
 L=75-1000mm
 Black or White
 PA6.6

**NYL5401**

↔ up to 4.8mm

**NYL5405**


↔ 3.5-12.5mm

**Cinturing Nylon Tie**

↔ 9mm
 L=200-760mm
 Black
 PA6.6

**Cush-a-Clamp**

Insulated Strut Clamp
 ø 6-160mm
 -45-135°C
 Zinc Plated or SS304

**Cush-a-Nator**

Insulated Strut Clamp
 ø 6-160mm
 -45-135°C
 Zinc Plated or SS304

**Cush-a-Nator HT**

High Temperature
 ø 6-160mm
 -53-170°C
 Zinc Plated or SS304

**Alpha**

Insulated U-Bolt
 ø 21-324mm
 Standard & High Temp.
 Zinc Plated or SS304

**Omega**

Insulated Strap Clamp
 6-168mm
 Standard & High Temp.
 Zinc Plated or SS304

**Klo-Shure
Clamps 8 Series**


ø 6mm-DN100
 For Use with Elastomeric
 Foam Insulation

**Klo-Shure
Clamps 8 Series**


ø 6mm-DN50
 For Use with Elastomeric
 Foam Insulation

**Bronco
Saddle Support**

ø 50-220mm External
 For Use with Elastomeric
 Foam Insulation

**Strut Channel**

on Request.

**Strut Fittings**

on Request.

**DIN3015
Beta Standard**

ø 6-102mm
 PP, PA, SA & Aluminium
 W1, W4, W5

**DIN3015
Beta Twin**

ø 6-42mm
 W1, W4, W5

**DIN3015
Beta Heavy**

ø 6-450mm
 W1, W4, W5

**DIN3015
Beta Smooth**

ø 6-102mm
 W1, W4, W5

**DIN3015
Beta Smooth Twin**

ø 6-42mm
 W1, W4, W5

**Cush-a-Bloc**

267x127x106mm
 LxWxH

**Cush-a-Bloc
& Strut**

41x21mm Strut

**Cush-a-Bloc
Bridge**

2 Blocks with
 Strut on Request

**Cush-a-Bloc
Mini**

168x127x102mm
 LxWxH

**Cush-a-Bloc
Mini & Strut**

41x21mm Strut

Product Details and Ordering Information:

Material		DIN	AISI	BS
W1	Steel, Zinc Plated			
W2	Band & Housing	1.4016	430	430 S 17
	Screw	Steel, Zinc Plated		
W3		1.4016	430	430 S 17
W4		1.4301	304	305 S 15
W5		1.4401	316	316 S 31

Explanation of Symbols

↔	Strap Width / Suitable For
∅	Clamping Range / Diameter
L	Length



clamp[®]
A TRIDON COMPANY



Products displayed in this flyer are RoHS compliant.
For detailed information please contact us.

Clamp s.r.l.

Via dell'Artigianato1

200070 Cerro al Lambro (Milano) Italy

T: +39 02 9803211 F: +39 02 980321399

www.clamp.it

